

IPC800

8.4inch Panel PC with Intel Chipset



Key Features

- ◆ 8.4" TFT LCD display with LED backlight
- ◆ Fanless design with Intel® Processor N-series
- ◆ Resistive Touch
- ◆ Default IP66 Front Waterproof
- ◆ 250nits Brightness, Upgradable to 1000nits
- ◆ Rich Expansion: 3G/4G, WIFI, Blooth, RS232/RS422/RS485, GPIO Options
- ◆ Embedded, Wall Mounted, Vesa

System Parameters

Processor&Chipset	<ul style="list-style-type: none">● Intel® Processor N-series● Onboard Intel® i3,i5,i7, 4th~9th Generation
Memory	1 x DDR3 /DDR4 SO-DIMM socket, 2GB/4GB/8GB/16GB
Storage	1 x 2.5" SATA 500GB/1TB/2TB 1 x Msata 16GB/32GB/64GB/128GB/256GB
Cooling System	Fanless design
BIOS	AMI 16MB DPI Flash
Watchdog Timer	255 level, 0~255 sec
LAN	1 x Realtek RT8111E, 10/100/1000M, Support PXE, Wake on Lan
Audio	Realtek ACL662 Audio controller, Line-out, Mic-in.
Expansion Port	2 x MINI PCI-E full slot, 1 x SIM
OS	Linux/ Win dows XP/7/8/10

Expansion Function

GPIO	Optional
3G/4G	Optional
WIFI/BT	Optional(802.11 a/b/g/n, Bluetooth 4.0)
RS422/485	Optional
Speaker	Optional

Degree of protection

Front Panel IP65	Default
Whole IP65	Optional

Display Parameters

LCD Size	8.4inch
Resolution	800*600
Brightness	250cd/m ²
Aspect ratio	4:3
Life Time	50,000hrs

Contrast Ratio	(500:1)
Response Time	10ms
Viewing Angle	70/60(U/D), 70/70(L/R)
Color Resolution	0.32

Touch Screen Parameters

Touch Type	Resistive type
------------	----------------

IO Interface

COM	5 x COM(Default RS232, 6 maximum)
RS422/485	Optional (1x RS485/422)
USB	2 x USB2.0
LAN	2 x RJ45, 10/100/1000M
Audio	Line-out, Mic-in
VGA	1x
HD MI	1x

Power Supply

Power Supply	12V DC Power Input
Power Consumption	<30W
Wide Voltage	Optional (DC 6~36V Wide Voltage, IPTS)

Installation

VESA	75mm*75mm
Embedded	Cabinet Hole Size: 195mm*150mm

Environments

Operating Temp	-10°C~50°C
Storage Temp	-30°C~70°C
Relative Humidity	5~95%@10°C (Non-condensing)
Vibration	5~500Hz,1.5G,0.15mm peak value
Shake	1.5 Grms, IEC 60068-2-64, 5 ~ 500 Hz, 1 hr/axis
Shock	10 Grems, IEC 60068-2-64, Half sine wave,for 11 ms
EMC	CE/FCC Class A

Enclosure

Housing Material	Aluminum Chassis with fanless design
Dimensions	205 mm (W) x 160 mm (D) x 56 mm (H)
Net Weight	3KG